

SUPRA SILENT

The quietest range of diesel units in the market.



SUPRA Silent

The new SUPRA Silent leads its class in low-noise emission, and retains the temperature management and reliability of conventional diesel technology.

Designed for 24/7 deliveries, even in noise-sensitive residential areas, the Silent system is available on a range of 3 units:

SUPRA 950 Silent
SUPRA 850 Silent
SUPRA 750 Silent

in 3 different versions:

- SUPRA** – Standard single-temperature
- Mt°** – Multi-temperature, for total flexibility in multi-product deliveries
- Nordic** – Nordic, with electrical & hot water heating, for extreme low ambient temperatures.

▶ Sound levels that are unheard of!

Noise levels are reduced by over 4dBA compared to previous generation models. That means 60% less noise!

▶ New internal design features

The Silent system integrates a design exclusive to Carrier Transicold.



SUPRA 950 SILENT ▶ up to 90 m³

SUPRA 850 SILENT ▶ up to 75 m³

SUPRA 750 SILENT ▶ up to 66 m³

▶ Exceptional reliability

Superior efficiency and enhanced product protection, even with frequent door openings.

▶ With all the **ease of use, service accessibility** and **exceptional cooling capacities** associated with the renowned SUPRA range.



SUPRA Silent has been the object of extensive acoustic research:

- ▶ Noise identified and eliminated at the source (new exhaust mechanism, air filter, muffler, silentblock platform)
- ▶ Residual sound trapped inside the unit (new sound-absorbing materials in doors, skins, improved air canalisation).

■ Refrigeration capacity ■ Airflow

Evaporator return air temperature	Operation (watts)				Airflow m ³ /h
	Road		Standby		
	0°C	-20°C	0°C	-20°C	
SUPRA 950 Silent	10 770	6 450	10 030	6 190	2 770
SUPRA 850 Silent	7 810	4 910	6 400	4 040	2 500
SUPRA 750 Silent	6 765	3 825	5 235	3 045	2 200

Ambient temperature at + 30 °C (per A.T.P. procedure)

■ Weight ■ Dimensions ■ Required opening

SUPRA Silent	Weight Kg	Dimensions mm	Required opening	
			Single temp.	Multi-temp.
SUPRA 950	596 – 625	1995 x 940 x 684	1245 x 350	100 x 100
Nordic	604 – 633			
Mt°	561 – 590			
SUPRA 850	455 – 477	1823 x 856 x 629	1245 x 350	90 x 90
Nordic	463 – 485			
Mt°	443 – 465			
SUPRA 750	423 – 445	1823 x 856 x 629	1245 x 310	90 x 90
Nordic	431 – 453			
Mt°	405 – 427			



CARRIER TRANSICOLD EUROPE S.A.S.
10, boulevard de l'Oise
F-95031 CERGY PONTOISE CEDEX
Phone: +33 (0)1 34 43 48 00 - Fax: +33 (0)1 34 43 48 48

www.carrier-transicold-europe.com

Carrier Transicold Europe S.A.S. au capital de 16 090 700 euros
R.C.S. Pontoise B 410 041 776 - Code APE 518M - VAT: FR52410041776
The information contained in this document is not contractually binding,
and may not be reproduced without prior approval.
Printed in France (11-03) 62-00000-00

500 CARRIER SERVICE STATIONS
in EUROPE, RUSSIA, MIDDLE EAST and AFRICA.



Carrier

A United Technologies Company